

Indoor 15m IR Dome Camera



Feature

- 1/4 Sharp II CCD; 12 Led
- Auto switch from Day to Night
- Built-in lens of 3.6 mm F1.5
- Good picture even at 0 Lux
- Easy installation
- Apply for 24 hours surveillance area

Specification

Item	HW-RS35/4SA
Image Sensor	1/4 inch Sharp II CCD
Sensor area	3.6 mm x 2.7 mm
Signal system	PAL
Effective Pixels	PAL: 500(H) x 582(V)
TV lines	420 TVL
Illumination	0 Lux (IR on)
Lens	3.6 mm F1.5
S/N Ratio	More than 48 dB
E-Shutter	1/50(1/60) ~ 1/100.000 (s)
White balance	Auto
Effective Distance	15 m
Video Output	1.0 Vp-p 75 Ω (BNC)
Power	DC 12 V ± 0.5% (250 mA)
Working Temperature	-10° C ~ +50° C
Size	80 x 80 x 93 mm
Gross weight	0.25 kg

ISAB INTERNATIONAL SECURITY AB

Headquarters:

Box 5129
SE-350 05
Växjö
Sweden
Tfn: (+46) (0)470 79 58 88
<http://www.is-ab.se>
Mail: info@is-ab.se
VAT: 5561099119023

Branch Torekov:

Junkersgatan 15
SE-260 93
Torekov
Sweden
Tfn: (+46) (0)431 36 44 70
<http://www.is-ab.se>
Mail: info@is-ab.se