

WiFi IP-Camera MJ543W



MJ-543W är en trådlös WiFi IP-kamera med många användningsområden. Kameran har en inbyggd webbserver som gör det möjligt att via Internet se bilder och styra kamerans olika funktioner när helst du vill. Uppkopplingen sker endera via fabrikantens server eller så väljer du någon annan fristående tjänst som t ex www.no-ip.com.

Kameran är försedd med IR-dioder för s/v bild i mörker. IR-dioderna kopplas in automatiskt vid skymning.

Kameran är enkel att installera och använda.

Specifications

- Support VGA / QVGA / QQVGA three resolutions, video quality class, video display layout, working environment and other parameters settings.
- MJPEG video compression.
- Built-in Wi-Fi, Support 802.11b/g protocol, and build up wireless monitoring.
- Built-in web server, support video view and parameter settings by browser; use one port to send all the data, it facilitates network setting.
- 24 infrared lights with 15m~25m night vision.
- Adopt Metal shell, the level of waterproof up to IP66.
- Support UPNP, port forwarding automatically on the router.
- Motion detection and alarm pin can be connected to external sensors to detect environmental situation.
- Send alarm messages by email and FTP to alarm server.
- Support three level of user authority.
- Support remote upgrade.
- Machine ID and DDNS are provided by manufacturer. You can visit the IP camera once connected to the internet.
- Provide free software, support Multi-view, Long time recording, video replay etc.

ISAB INTERNATIONAL SECURITY AB

Headquarters:

Box 5129
SE-350 05
Växjö
Sweden
Tfn: (+46) (0)470 79 58 88
<http://www.is-ab.se>
Mail: info@is-ab.se
VAT: 5561099119023

Branch Torekov:

Junkersgatan 15
SE-260 93
Torekov
Sweden
Tfn: (+46) (0)431 36 44 70
<http://www.is-ab.se>
Mail: info@is-ab.se

Technical parameters

Item	Sub item	Specification
Image Capture	Sensor	1/4" CMOS sensor
	Total of pixel	300,000
	Minimum illumination	IR lights on, 0 Lux
	Lens	f=6.0 mm, F=2.0, standard infrared lens
Assistant	Lighting Control	Auto control
	Lighting	24 pcs 850 nm Infrared lights, 25 m night-vision
Video and Audio	Resolution	VGA (640*480) QVGA (320*240) QQVGA(160*120)
	Compression	MJPEG
	Frame rate	30 fps
	Material	Iron
	Image Rotation	Flip / Mirror
	OSD	Support
Network	Audio Compression	ADPCM
	Basic Protocol	TCP/IP, UDP/IP., HTTP, SMTP, FTP, DHCP, DDNS, UPNP, NTP, PPPOE
	Other Protocol	802.11b/g (Wireless IP camera)
Other Features	Mobile Phone View	Support
	Video control	Support
	Dual way audio	Support
	Triggered Actions	Email / FTP / SD storage / external alarm / send message to alarm server
	User Setting	Three levels
	Date/ Time Setting	Support
	Upgrade	Upgrade from network
	DDNS	A free DDNS provided by manufacturer
Physical Index	Weight	610 g
	Material	Iron
	Main body (LxWxH)	185 mm * 75 mm * 80 mm
	Power	DC 6V
	Power consumption	<6W
	Operating temperature	-20°C~ 45°C
	Humidity	10% ~ 80% non-condensing
Software (PC Side)	OS Supported	Microsoft Windows 98/2000/XP/Vista, windows 7
	Browser	Internet Explorer 6.0 and above or Compatible Browser, Safari / Firefox etc.
	Application Software	IPC Monitor.exe