



DOOR AND GATE CONTROL EQUIPMENT

CGO-1 CGO-1 KIT

HTX006/4 transmitter

4 CHANNEL DOOR CONTROL
PANEL

WITH FOUR BUTTON REMOTE
CONTROL



Applications

Control panel for remote or manual.
Operation of gates, doors, shutters etc.
Specifically for use with tubular motors.

Compatible Products

NIR-100 Photoelectric Beam Sensor with
transceiver and reflective plate.
Range 7 m

Foto 15 Photoelectric Beam Sensor with
receiver and transmitter. Supplied with 30 m
cable.
Range 15 m

Foto 30 Photoelectric Beam Sensor With
receiver and transmitter.
Range 30 m

Features

- 3 separate functions of OPEN, STOP, CLOSE
- Connects to standard tubular motors
- External courtesy light switched upon activation of Open or Down function
- Selectable ON time of 90 or 180 seconds of courtesy light
- Input the emergency STOP button
- Input for safety photocells (12V DC or 24V DC)
- Input for alarm
- Connector for remote keyswitch or keypad
- Manual operation via push button or remote operation via remote control
- Receiver learns up to 30 different remote controls
- Button 4 of remote control toggles ON/OFF either a pcb relay (for remote activation of additional light etc.) or the receiver self-learn function
- Receiver learns up to 30 different remote controls
- Separate LED indication on pcb to show: AC on Channel 4 on Motor on Open Courtesy light on
- LED to indicate good reception of signal and/or transmitter low battery
- Di-pole antenna configuration for optimum performance
- Narrow band super-heterodyne receiver 433MHz

ISAB INTERNATIONAL SECURITY AB

Headquarters:

Box 5129
SE-350 05
Växjö
Sweden
Tfn: (+46) (0)470 79 58 88
<http://www.is-ab.se>
Mail: info@is-ab.se
VAT: 5561099119023

Branch Torekov:

Junkersgatan 15
SE-260 93
Torekov
Sweden
Tfn: (+46) (0)431 36 44 70
<http://www.is-ab.se>
Mail: info@is-ab.se