



## Indoor suspended Intelligent Middle Speed Dome Camera

### **Model: DH 9300**

Parameter	Description
Image Sensor	CNB Camera 3.6 mm (H) × 2.7 mm (V) 1/4 SONY super HAD CCD
Lens	22 ggr Zoom Video AF (F1.6, f=3.6 ~ 82.8 mm)
Signal System	PAL
Effective Pixels	480 TVL / 570 TVL (B/W)
Video Output	1 Vp-p BNC
Minimum Illumination	1.0 Lux (Color) 0.1 Lux (B/W)
Iris	Auto
Backlight compensation	Auto
Digital Zoom	22 ggr 10
BLC	ON/OFF
White Balance	Auto Tracking Balance
S/N Ratio	Better than 48 dB (AGC OFF)
Control	Up & Down, Left & Right, 64 presets
Left & Right Rotation Range	360°
Left & Right Speed	0.1° — 120°/sec
Up & Down Rotation Range	0° — 90° 90° Vertical auto overturn
Up & Down Speed	0.1° — 80° /sec
Control Method	RS 485
Electronics Shutter	1/50 ~ 1/10,000s (Manual, 8 steps)
Shutter speed	One line patrol track *
Power Input	AC 24V
Dimension	H: 172 mm, Base dia:185 mm, Cover dia: 152 mm
Weight	About 3,3 kg

\*You can setup one patrol track to cycle.

### **ISAB INTERNATIONAL SECURITY AB**

**Headquarters:**

Box 5129  
SE-350 05  
Växjö  
Sweden  
Tfn: (+46) (0)470 79 58 88  
<http://www.is-ab.se>  
Mail: [info@is-ab.se](mailto:info@is-ab.se)  
VAT: 5561099119023

**Branch Torekov:**

Junkersgatan 15  
SE-260 93  
Torekov  
Sweden  
Tfn: (+46) (0)431 36 44 70  
<http://www.is-ab.se>  
Mail: [info@is-ab.se](mailto:info@is-ab.se)